

# TecJet™ 52 Gen II

## Intelligent Electronic Gas Metering Valve

### Description

Efficiency, performance, and emissions. In today's marketplace, these factors play a key role in gas engine development. As engine performance advances are made, gas metering devices should be more flexible and accurate, and be used for a wide range of gas qualities from butane down to landfill gas.

The TecJet™ is an electronic gas metering valve for single-point injection. It has integrated sensors and electronics, which provide the correct gas flow under all specified conditions.

In general, a separate engine control system, like the E3 control, calculates the desired gas flow from the different engine and gas parameters. This desired gas flow is transmitted through a CAN link to the TecJet valve(s). The TecJet valve ensures that the desired gas flow is attained, automatically compensating for changes in gas pressure and gas temperature.

The microcomputer inside the TecJet valve converts the desired gas flow signal and gas parameter information into a valve position (which corresponds to the desired gas flow), depending on gas inlet pressure, gas temperature, and the pressure difference across the valve.

### Benefits

Flexible inputs to use the engine control system of an OEM. Communication in two directions possible with other control systems by means of the integrated CANbus.

Fast response to flow commands, which makes it possible to accept large load steps without losing engine speed.

High turn-down ratio that makes it possible to use one TecJet model for a complete engine family.

### Application

The TecJet™ valve, together with an engine control system, form an ideal combination for operating gas engines with a gas specific gravity from 0.4 to 2.0. The TecJet 52 gas control valve is applicable for stationary applications within a power range of 210–800 kW for low-BTU specialty gas and 500–1500 kW for pipeline-quality natural gas. This range is also dependant on other factors such as fuel pressure, fuel differential pressure across the valve, fuel temperature, etc. Consult the applicable TecJet Installation and Operation manual or a Woodward application engineer for actual sizing of a valve.



- Enable fuel blending when used in conjunction with Woodward E3 fuel blending system
- Improved water ingress (UL/CSA Type 4) over previous generation
- Drop-in replaceability with previous TecJet 52
- New platform has smaller package size and lower weight, with multiple mounting options
- Improved, contamination- and sour-fuel-resistant shaft sealing
- Bi-directional communication via CANbus, CANopen, J1939, or custom CAN
- Improved dynamic response & repeatability over TecJet 50 Plus and TecJet 52
- Flow testing ensures that the engine does not have to be recalibrated if TecJet is replaced
- Compensates for gas pressure and gas temperature fluctuations
- Fully backward compatible with the TecJet 50 Plus and TecJet 52



## Specifications

Weight:	14.7 kg (32.5 lb)
Size:	52 mm
Valve Maximum Geometric Area:	1310 mm <sup>2</sup> (2.03 in <sup>2</sup> )
Input Voltage Range	18–32 Vdc
Input Current Range:	=1 A @ 24 Vdc steady state, 3.75 A @ 24 Vdc transient
Temperature Ranges	
Steady State Ambient:	–20 to +85 °C (–4 to +185 °F)
Long Term Storage:	–40 to +40 °C (–40 to +104 °F)
Short Term Storage:	–40 to +105 °C (–40 to +221 °F)
Fuel Gas Inlet:	0 to +85 °C (+32 to +185 °F)
Pressure Ranges	
Fuel Gas Inlet:	876 to 1289 mbar absolute (12.7 to 18.7 psia)
Inlet to Outlet Delta *:	69 to 345 mbar (1 to 5 psid)
Required Filter in the Gas Stream	Maximum mesh size 50 µm
Flow Accuracy *	±20% point accuracy -> Crank to Idle flow rate ±10% point accuracy -> Idle to 25% valve maximum rated mass flow ±6% point accuracy -> >25% valve maximum rated mass flow

\*—Add an additional 1.5%, 1%, and 0.5%, respectively, to flow accuracy values listed if inlet to outlet delta is greater than 276 mbar (4 psid).

Dynamics	
Position Response:	–3 db at > 7 Hz, with 1400%/second slew rate limit, 2 ms dead time. Overshoot < 1%
Demanded Flow Response:	Same as position loop response with addition of 3 ms flow loop update rate
Pressure Change Rejection:	Same as demanded flow response with addition of 10 ms lag on P1 measurement, 100 ms lag on delta pressure
Vibration:	Random Vibration: Exceeds WGC RV2, 10–2000 Hz @ 0.1 G <sup>2</sup> /Hz (12.8 Grms)
Shock:	Per US MIL-STD-810C, Method 516.2, Procedure 1 (40 g)
Communication/Command Signals:	CAN PWM: 7 to 32 V differential input, 12 bit resolution, 40 kΩ impedance 4 to 20 mA Analog: 225 Ω impedance, differential, 25 mA ±2% max input current Customer specific input

### Regulatory Compliance

European Compliance for CE Mark:

EMC Directive: Declared to 2004/108/EC COUNCIL DIRECTIVE of 15 December 2004 on the approximation of the laws of the Member States relating to electromagnetic compatibility and all applicable amendments.

North American Compliance: Product also complies with the Machinery and Pressure Equipment Directives.  
CSA Certified for use in Class I, Division 2, Groups A, B, C, and D T3 for United States and Canada as a component for use in other equipment.  
Type 4 Enclosure Watertight

TecJet Service Tool: The TecJet Service Tool can be downloaded from the Web at [www.woodward.com/software](http://www.woodward.com/software). Select software product “TecJet Tools”, then follow the installation instructions given on that page.

**Technical Manual:** 26833

For information about the larger **TecJet 110** (105 mm), please see product specification 03317.

## Adjustments

Using the TecJet Service Tool installed on a laptop or PC connected to the TecJet valve, you can monitor and make adjustments quickly and easily through the following six tabs:

### Overview Tab

The Overview Tab contains flow demand, gas pressures, gas temperature, and gas property information.

### Troubleshooting Tab

The Troubleshooting Tab contains typical valve information used for troubleshooting purposes. This information includes electronics temperature, supply voltage, running hours, and CAN communication info.

### Warnings Tab

The Warnings Tab displays valve warning indicators. When one of these warnings occurs, the valve continues to operate, but the valve Status Output switches to signal the operator that a problem has occurred.

### Errors Tab


The Errors Tab displays valve error indicators. When one of these errors occurs, the valve goes into shutdown mode, and the valve status output switches to signal the operator that a problem has occurred.

### Configuration Tab

The Configuration Tab allows the user to customize the valve to a particular application. CAN parameters, demand signal scaling, warning/error limits, default pressures, and demand source can all be viewed or changed on this tab.

### Identification Tab

The Identification Tab contains valve and software information such as part numbers and serial numbers.



**TecJet Monitoring Program**



PO Box 1519, Fort Collins CO, USA 80522-1519  
 1000 East Drake Road, Fort Collins CO 80525  
 Tel.: +1 (970) 482-5811 ♦ Fax: +1 (970) 498-3058  
[www.woodward.com](http://www.woodward.com)

#### Distributors & Service

Woodward has an international network of distributors and service facilities. For your nearest representative, call the Fort Collins plant or see the Worldwide Directory on our website.

This document is distributed for informational purposes only. It is not to be construed as creating or becoming part of any Woodward contractual or warranty obligation unless expressly stated in a written sales contract.

Copyright © Woodward 2014, All Rights Reserved

For more information contact: